



HH & HX Baler Specifications and Dimensions

(800) 678-7320

sales@jv.com

Cram-A-Lot HH-HX Series SPECIFICATIONS		HH-60	HX-60	HX-72	HX-72-W
Nominal Bale Size	Length	60"	60"	72"	72"
	Width	30"	30"	42"	48"
	Height	40"	40"	28"	48"
Clear Top Opening (W x L)		30"x 39 1/2"	30"x 39 1/2"	42"x 52 1/2"	48"x 64 1/2"
Bale Weight Up To (OCC)		1,100 lbs	1,400 lbs	2,200 lbs	2,400 lbs
Throughput (OCC)		2.5 bales / hr	2.5 bales / hr	2.5 bales / hr	2.5 bales / hr
Cycle Time (No Load)		24 sec	24 sec	24 sec	28 sec
Platen Force	Normal	76,900 lbs	107,700 lbs	100,500 lbs	100,500 lbs
	Max	92,300 lbs	119,300lbs	120,600 lbs	120,600 lbs
Platen Face Pressure	Normal	65.2 psi	91.3 psi	50.5 psi	44.1 psi
	Max	78.2 psi	101.1psi	60.5 psi	52.9 psi
Motor - 3 Phase	208/230/460 VAC	20 hp	25 hp	30 hp	30 hp
Pump Capacity		37.5 gpm	37.5 gpm	63 gpm	63 gpm
Hydraulic Reservoir	Capacity	105 gal	105 gal	180 gal	180 gal
Hydraulic Cylinder	Bore Dia.	7"	7"	8"	8"
	Stroke	54"	54"	70"	82"
	Rod Dia.	4"	4"	5"	5"
Operating Pressure	Normal	2,000 psi	2,800 psi	2,000 psi	2,000 psi
	Max	2,400 psi	3,100 psi	2,400 psi	2,400 psi

Cram-A-Lot HH-HX Series DIMENSIONS	Overall Height w/ Standard Hopper	Overall Height w/ Conveyor & Hopper	Overall Width	Overall Length with Door Open	Overall Length with Door Open & Conveyor	Unit Weight
HH-60	10' 1"	7' 7"	3' 10"	19' 2"	31' 6 1/2"	13,000 lbs
HX-60	10' 1"	7' 7"	3' 10"	19' 2"	31' 6 1/2"	13,500 lbs
HX-72	11' 11"	8' 4"	5'	24' 2"	37' 5 1/2"	15,900 lbs
HX-72-W	12' 1 1/2"	8' 4"	5' 6"	26' 2"	31' 6 1/2"	16,500 lbs