

ST-75 2-Shaft Shredder

The ST-75's revolutionary design allows it to easily shred steel drums, auto tires, castings, medical and hazardous waste, high volume confidential waste and many other materials.

It does more so you can DO MORE!



STANDARD FEATURES

CUTTING CHAMBER

The redesigned ST-75 shredder has a choice of cutting chamber size, 50 1/8" x 25" or 37 5/8" x 25", enabling it to handle a wide range of product sizes.

DRIVE SYSTEM

The ST-75 is available with a wide range of gear reduced electric or hydraulic drives. The electric model has two 30, 40 or 50 HP motors. The hydraulic model is equipped with high torque, low speed, multi-cam, radial piston motors.

KNIVES

Shred-Tech Engineers design each knife profile and configuration to suit the material for maximum throughput and optimum shred size.

CONTROL PANEL


The ST-75 control panel, designed and fabricated by certified Shred-Tech technicians, features illuminated function buttons, keyed power switch, fused lockable disconnect, hour meter and a programmable logic controller for shredder functions including knife reversal on overload.

HOPPER AND STANDS

Quality is evident in the workmanship of Shred-Tech's extra heavy duty stand and hopper. As an option, the stand and hopper can be modified to suit the application or installation.

HEX SHAFTS

The unique design of the machined hex shafts maximizes knife placement options and allows for easy knife removal and machine maintenance. Size for size, the hex shaft is several times stronger than a keyed shaft. The Shred-Tech hex shaft drive system offers the highest knife tip cutting force of any comparable shredder on the market.



SHRED-TECH



ST-75

2-Shaft Shredder

The ST-75 is designed for maximum use with a wide range of materials and optimum shred size.

SHREDDER TECHNICAL SPECIFICATIONS

	ST-75E	ST-75H	ST-75ES	ST-75HS
MEASUREMENTS				
M/C Length	134"	99"	121"	86"
M/C Width	51"	51"	51"	51"
M/C Height	105"	105"	105"	105"
M/C Weight (lbs)	8,400	6,900	7,600	6,100
Floor Space (sq.ft.)	48	35	43	31

PRODUCT SPECIFICATIONS				
Drive	Electric	Hydraulic	Electric	Hydraulic
Number of Motors	2	2	2	2
Horsepower	60-100	75	60-100	75
Voltage (3 Phase)	208-600	208-600	208-600	208-600
Hertz	50/60	50/60	50/60	50/60
Knife Thickness (STD)	5/8" 1" 1 1/2"	5/8" 1" 1 1/2"	5/8" 1" 1 1/2"	5/8" 1" 1 1/2"
Number of Knives	72 48 32	72 48 32	54 36 24	54 36 24
Knife Diameter	12 1/2"	12 1/2"	12 1/2"	12 1/2"
Hex Size	4 5/16"	4 5/16"	4 5/16"	4 5/16"
Distance Between Shafts	9 7/16"	9 7/16"	9 7/16"	9 7/16"
Cutting Chamber	50 1/8" x 25"	50 1/8" x 25"	37 5/8" x 25"	37 5/8" x 25"
Discharge Height	42"	42"	42"	42"
Hopper Height	34"	34"	34"	34"
Hopper Opening	50" x 46"	50" x 46"	38" x 46"	38" x 46"
Stand Opening	25"	25"	25"	25"
Stand Opening	76"	76"	64"	64"

OPTIONAL FEATURES

- PLC Interfacing for Peripheral Equipment
- Custom Stands and Hoppers
- Feed and Discharge Conveyors
- Pneumatic or Hydraulic Ram
- Modem Capabilities
- Trailer Mounted
- Vibrating, Magnetic or Rotary Separation
- Reduced Voltage Starters
- Service Platform
- Explosion Proof Motors

MAINTENANCE

Several design refinements proven successful to increase ease of maintenance and shredder durability in Shred-Tech's model line up have been incorporated into the ST-75 shredder. The new torque tube body design, in combination with increases in shaft hex thickness, knife diameter and spacer thickness, have resulted in superior durability and higher service factors. Bulkhead walls and labyrinth barriers at either end of the cutting chamber provide excellent bearing and seal protection. Sectional cleaning fingers, which are removable from the top, and a light weight chamber plate ensures cutting chamber disassembly is quick and easy. Bearing and seal replacement is easily completed without the need of gearbox disassembly.


Product specifications subject to change without notice.

>> All Shred-Tech Shredders are available under US Federal Supply Contract.® All rights reserved. Shred-Tech and Shred-Tech logo are registered trade-marks of Shred-Tech.

>> SHRED-TECH. COMPLETE INFORMATION DESTRUCTION AND RECYCLING SOLUTIONS.

W www.shred-tech.com | E shred@shred-tech.com | T 800.465.3214 or 519.621.3560 | F 519.621.4288

SERVICE HOTLINE 877.566.2345



SHRED-TECH